


**Product Image**



**Product Dimensions**



**Characteristics**

Nominal Voltage		12V
Nominal Capacity (10 hour rate)		180Ah
Capacity 25°C (77 F)	10 hour rate (10.0A)	199.8Ah
	5 hour rate (32.94A)	166.1Ah
	1 hour rate (119.7A)	119.7Ah
Internal Resistance	Full Charged Battery 25°C	≤5.0mΩ
Capacity affected by Temperature (10 hour)	40°C (104 F)	102%
	25°C (77 F)	100%
	0°C (32 F)	85%
	-15°C (5 F)	65%
Self-Discharge 25°C (77 F) Capacity	after 3 month storage	90%
	after 6 month storage	80%
	after 12 month storage	62%
Charge (Constant Voltage) 25°C (77 F)	Float	Initial Charging Current Less than 75.6A Voltage 6.8-6.9V
	Cycle	Initial Charging Current Less than 75.6A Voltage 7.2-7.45V

**Packaging**

Battery Dimensions	Length	260mm
	Width	180mm
	Height	245mm
	Total Height	251mm
Box Dimensions	Length	275mm
	Width	194mm
	Height	305mm
Quantity Per Box		1 PC per box
Net weight Per Cell		29.5kg ±400g
Net weight Per Box		29.5kg
Gross Weight		30kg

**恒电流放电参数表 (25° C)**





终止电压/单格	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1. 60V	499.0	318.1	270.3	172.6	126.8	116.4	53.2	52.0	35.3	23.3	20.8	11.5
1. 65V	489.9	312.3	265.4	169.4	124.5	114.3	52.3	51.0	34.7	22.9	20.4	11.3
1. 70V	480.8	306.5	260.4	166.3	122.2	112.2	51.3	50.1	34.1	22.4	20.0	11.1
1. 75V	471.7	300.7	255.5	163.1	119.9	110.1	50.3	49.1	33.4	22.0	19.7	10.9
1. 80V	453.6	289.2	245.7	156.9	115.3	105.8	48.4	47.3	32.1	21.2	18.9	10.50

**恒功率放电参数表 (25° C)**

终止电压/单格	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1. 60V	960.5	612.3	520.3	332.2	244.1	224.1	102.5	100.1	68.0	44.8	40.0	22.2
1. 65V	943.0	601.2	510.8	326.1	239.7	220.0	100.6	98.2	66.8	44.0	39.3	21.8
1. 70V	925.6	590.1	501.4	320.1	235.2	216.0	98.7	96.4	65.6	43.2	38.6	21.4
1. 75V	908.1	578.9	491.9	314.1	230.8	211.9	96.9	94.6	64.3	42.4	37.8	21.0
1. 80V	873.2	556.7	473.0	302.0	221.9	203.7	93.1	91.0	61.9	40.7	36.4	20.2

**Note** The above data are average values, and can be obtained within 3 charge/discharge cycles. These are not minimum values. Cell and battery designs/specifications are subject to modification without notice. Contact **US** for the latest information.

**Performance Characteristics**



**Battery Construction**

Component	Positive plate	Negative plate	Container	Cover	Safety valve	Terminal	Separator	Electrolyte
Raw material	Lead dioxide	Lead	ABS	ABS	Si-Rubber	Lead	Fiberglass	Colloid(GEL)

**Guangzhou Hengda Battery Co.,Ltd**

Tel: 020-84866132 02084866098 Fax: 020-84869892  
021-52811136; 021-52826931; 021-52826931-19